

Porous materials in heat storage and reallocation applications

Natasa Zabukovec Logar

University of Nova Gorica - National Institute of Chemistry, Slovenia

Thermal energy storage is recognized as one of the crucial technologies for enabling more efficient use of fossil fuels and renewable energies by providing the supply-demand balance. Thermochemical heat storage (TCS), which utilise the reversible chemical and physical sorption of gases, mostly water vapour, in solids, is currently considered as the only storage concept with a potential for long-term, also seasonal, heat storage of high enough storage density to be also economical and attractive. Under the influence of a heat supply in TCS, water is desorbed from the material, which is then stored separately (an endothermic phenomenon referred to as the charging or activation of material). When water vapour and sorbent are put into contact, there is a heat release (an exothermic phenomenon referred to as a material's discharge or deactivation). The TCS has a potential to enable an extensive use of a solar thermal energy and residual heat from industry, thus leading to a low carbon energy society. Over the last decade, a lot of attention has been devoted to the development of porous adsorbents, like zeolites, microporous aluminophosphates and metal-organic framework materials for water-adsorption-based thermal energy storage and heat transformations. A good sorption-based energy-storage material should fulfil the following requirements: (i) it should exhibit high water uptake at low relative humidity, (ii) it should be easily regenerated at low temperature, and (iii) it should be highly hydrothermally stable and should enable good cycling (adsorption/desorption) performance. Recently, we have focused our research on the development of porous materials for water-adsorption-based thermal energy storage and heat transformations.

Advanced Energy Materials and Research

through in-situ metal-oxide recrystallization. *Journals of Materials Chemistry A* 5:1967-1971.

4. Krajnc et al. (2015) A simple NMR-based method for studying the spatial distribution of linkers within mixed-linker metal-organic frameworks. *Angewandte Chemie* 54(36):10535–10538.
5. Ristic et al (2012) The performance of small-pore microporous alumino phosphates in low-temperature solar energy storage: the structure-property relationship. *Advanced Functional Materials* 22(9):1952-1957.

Biography

Nataša Zabukovec Logar is a Head of the Department of Inorganic Chemistry and Technology at the National Institute of Chemistry in Ljubljana and Full Professor of Chemistry at the University of Nova Gorica. She obtained her PhD from University of Ljubljana in 1998. In 1995 and 1996 she was a visiting student at the University of Manchester, UK and in 2014, a visiting researcher at the Center for applied energy research in Munich, Germany. She has more than 20 years of experience in the research in the field of porous materials for energy and environmental applications. Her research emphases are development of new materials for gas and heat storage, and studies of metal sorption on porous solids for their use in wastewater and drinking water treatment. She is a treasurer of European Federation of Zeolite Associations and a member of the Synthesis Commission of the International Zeolite Association.

natasa.zabukovec@ki.si