Innov Ener Res 2018, Volume 7 DOI: 10.4172/2576-1463-C1-003

Advanced Energy Materials and Research

Donglu Shi and **Yuan Zhao** University of Cincinnati, USA

ISSN: 2576-1463

To prevent heat loss through windows in cold climates, the conventional methods mainly rely on low-e coatings and thermal insulating materials on double-pane windows. In this study, naturally occurring chlorophyll is utilized as a thin lm coating on glass (also known as "Green Window" for its natural and green appearance) and demonstrates applicability to signi cantly reduce thermal loss, thus improving energy savings. Chlorophyll exhibits a unique optical characteristic with strong absorptions in the blue-violet and NIR regions while remaining highly transmissive in much of the visible region. is unique property allows, on one hand, simulated solar energy, in the non-visible region, to be converted to heat by chlorophyll through the so-called photothermal e ect. Only slight heating due to the photothermal e ect on the window surface is required to signi cantly reduce the U-factor (related to thermal loss). On the other hand, the chlorophyll coating density required to generate this temperature rise by thin lm deposition on glass retains high light transmittance attributable to minimum absorption in the visible range. is concept li s the dependence on insulating materials making single-pane windows highly possible. Chlorophyll synthesis, thin lm deposition, optical characterization, photothermal e ect, and energy performance quanti cation are carried out in this study with engineering considerations in window designs.

donglu.shi@uc.edu

Innovative Energy & Research Volume 7