Constructed Wetlands and their Role in Remediation of Industrial Effluents *via* Plant-Microbe Interaction – A Mini Review

Filza Hussain[1*], Ghulam Must fa[1], Rabisa Zia[1], Ali Faiq[1], Madeeha Matloob[1], Haseeb-ur-Rehman Shah[1], [2] and Jazib Ali Irfan[2*]

[1]Soil and Environmental Biotechnology Division, National Institute for Biotechnology and Genetic Engineering (NIBGE), Faisalabad, Pakistan

[2]Agricultural Biotechnology Division, National Institute for Biotechnology and Genetic Engineering (NIBGE), Faisalabad, Pakistan

*[*]**Corresponding authors:** Filza Hussain, Soil and Environmental Biotechnology Division, National Institute for Biotechnology and Genetic Engineering (NIBGE), Faisalabad, Pakistan, E-mail: filzahussain786@gmail.com*

Jazib Ali Irfan, Agricultural Biotechnology Division, National Institute for Biotechnology and Genetic Engineering (NIBGE), Faisalabad, Pakistan, Tel: +923465449709; E-mail: jazibali10@yahoo.com

Rec date: May 11, 2018; **Acc date:** June 18, 2018; **Pub date:** June 20, 2018

Copyright: © 2018 Hussain F, et al. This is an open-access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

Abstract

Phytoremediation has proven to be an efficient, widely used and adopted method for the treatment of wastewaters and soil in the form of Constructed Wetlands (CWs). Plant-microbe interaction can be utilized to overcome the increasing health hazards due to the increase in pollution. Plants have the ability to live in a mutual relationship with many different kinds of microbes. Most of them live and interact with the roots of plants and that part of the plant seems very important in overcoming the conditions of less water, excessive evapotranspiration, rapid nutrient loss etc. Microbes, mostly bacteria interact with the roots of the plants and degrade the minerals and materials present in the soil in order to obtain energy for themselves. Plants get benefit from the microbial activities as they can utilize the minerals degraded by the root-colonizing bacteria. Root-colonizing bacteria can either be endophytic or ectophytic. The main focus of this review is on the bacteria that synergistically help the plant to degrade the minerals present in the surrounding pollutants and in return gets shelter and exudates from the plants. Removal of industrial effluents from the soil and water is necessary because they seem to have been causing several toxicity problems in the soil microbiota, plants as well as in the humans that consume them.

Keywords: Constructed wetlands; Industrial e f uents; Waste-water; Synergism; Plant-microbe interaction

Introduction

Constructed wetlands (CWs) are an alternative method for wastewater treatment and its puri f cation. In the past decades, CW techniques were hardly used for contamination removal [1,2], although f rst time in early 1950s, Dr. Kathe Seidel used constructed wetland for wastewater treatment [3]. But evolutionary period started since the 1990s, this technique is used to treat various types of wastewaters i.e., industrial e f uents, municipal wastewater, and drinking waters. CWs are the engineered systems that mimics the natural processes by removing the pollutants or by reducing the level of pollutants to a dischargeable limit [4].

Constructed wetland treatment systems e f ciently remove several kinds of pollutants from wastewater, drinking water, and industrial e f uents [5-7] within the controlled environment and are considered as environment-friendly. Removal of e f uents, metal and waste are performed through a variety of processes i.e., by increasing sorption, hydrolysis, f ltration and oxidation, precipitation, binding with iron oxide, microbial activity and uptake by plants. In response to removing pollution, constructed wetlands di f er in their processes, cost e f ectiveness and their design [8] and also enhance the waste removal performance by using di f erent substrates i.e., Phosphorus (P) [9]. In the recent years, scientists have tried to remediate or clean up wastewater through phytoremediation and bioremediation. Constructed wetland treatment systems use microbes and rooted plants to remove contaminants from soil or wastewater. It takes advantage of natural wetland processes (biological [10], physical and chemical processes [11]) to remove contaminants [12] but the e f ciency of all the processes (Chemical, physical and Biological) di f er with water residence time.

T is technology is now widely used (in America, China, Argentina, Czech Republic, Greece, Netherlands, and Europe [13-15]) and tested to e f ciently improve water quality. However, the industrial and environmental sector pay more attention to remove heavy metals form industrial e f uents using CWs [7,16,17]. CWs are more e f ective and have signi f cantly low capital costs as compared to conventional system (ITRC 2003) and also require less labor and electricity to operated (USEPA 1988). aT e]